



# PURO<sup>G4</sup>

## Indoor Oyster Lights



**POWER**  
Switchable  
Modes



**TRITONE**  
Colour  
Changeable



**IP54**  
Ingress  
Protection  
Rating



**120°**  
Beam  
Angle



**50,000hr**  
Projected  
Lifetime



**5yr**  
Warranty

### General Purpose Oyster Lighting

The **PURO G4** LED oyster light is designed to provide smooth light distribution and tritone colour capabilities. Available in different sizes and the option of combining a sensor option, the PURO G4 is a perfect all-round oyster light.

#### Features

- Tritone colour changeable
- Dimmable Driver
- Flicker-free driver
- IP54 rating (from below)
- Choice of sizes to choose from
- Easy terminal block access
- Sensor activation (Model Dependent)
- Extensive model range
- High ambient temperature rating (>40°C)

#### Benefits

- Provides the choice of light hues from a single luminaire;
- Adjustable brightness to improve comfort;
- Increase productivity and lowers eye strain;
- Suitable for wet rooms such as bathrooms & laundries;
- Adaptable to suit various requirements;
- Aids in improving the installation process;
- Improve power conservation when not in use;
- Covers a diverse range of applications;
- Long lasting in hot environments;

**Product Overview**

POWER	LUMENS	EFFICACY	CCT	WEIGHT	SAP CODE	PRODUCT CODE
8 W 10 W 11 W	680 / 752 / 730 lm 890 / 979 / 950 lm 960 / 1112 / 1080 lm	91 / 100 / 97 lm/W 94 / 103 / 100 lm/W 87 / 101 / 98 lm/W	3000 / 4000 / 5700 K	0.4 kg	2002371	<b>PURO11W-250R</b>
8 W 10 W 11 W 14 W	680 / 752 / 730 lm 890 / 979 / 950 lm 980 / 1082 / 1050 lm 1200 / 1391 / 1350 lm	91 / 100 / 97 lm/W 94 / 103 / 100 lm/W 89 / 98 / 95 lm/W 86 / 99 / 96 lm/W		0.54 kg	2002372	<b>PURO14W-300R</b>
8 W 10 W 11 W 15 W	680 / 752 / 730 lm 890 / 979 / 950 lm 980 / 1082 / 1050 lm 1200 / 1391 / 1350 lm	85 / 94 / 91 lm/W 89 / 98 / 95 lm/W 85 / 94 / 91 lm/W 83 / 99 / 93 lm/W		0.55 kg	2002373	<b>PURO14W-300R-MS</b>
9 W 12 W 18 W	850 / 927 / 900 lm 1120 / 1236 / 1200 lm 1700 / 1854 / 1800 lm	94 / 103 / 100 lm/W 93 / 103 / 100 lm/W 100 / 109 / 106 lm/W		0.60 kg	2002374	<b>PURO18W-350R</b>
9 W 12 W 18 W	850 / 927 / 900 lm 1120 / 1236 / 1200 lm 1700 / 1854 / 1800 lm	89 / 98 / 90 lm/W 90 / 99 / 96 lm/W 97 / 106 / 103 lm/W		0.61 kg	2002375	<b>PURO18W-350R-MS</b>
11 W 14 W 22 W	1080 / 1185 / 1150 lm 1360 / 1494 / 1450 lm 2125 / 2318 / 2250 lm	98 / 108 / 105 lm/W 97 / 107 / 104 lm/W 97 / 105 / 102 lm/W		0.83 kg	2002376	<b>PURO24W-400R</b>
11 W 15 W 23 W	1080 / 1185 / 1150 lm 1360 / 1494 / 1450 lm 2125 / 2318 / 2250 lm	94 / 103 / 100 lm/W 94 / 103 / 100 lm/W 94 / 105 / 100 lm/W		0.84 kg	2002377	<b>PURO24W-400R-MS</b>
25 W	2125 / 2415 / 2250 lm	85 / 97 / 90 lm/W		1.35 kg	2001991	<b>PURO25W-EM-MS</b>
25 W	2000 / 2220 / 2250 lm	85 / 97 / 93 lm/W		1.35 kg	2001989	<b>PURO25W400R-EM</b>

Oysters

SPECIFICATIONS		APPLICATIONS	
Body Material: Steel	Driver: Integral	<b>Bedroom</b> <b>Lounge Room</b> <b>Dining Area</b> <b>Laundry</b> <b>Hallway</b> <b>Staircase</b> <b>Walk-In Wardrobe</b> <b>Garage</b> <b>Education Facilities</b> <b>Hotel Common Areas</b> <b>Hotel Rooms</b> <b>Store Rooms</b> <b>Temporary Installations</b>	
Diffuser Material: PMMA	Connection Type: PA14 Terminals		
Body colour: White	Input: 220-240Va.c. 50/60Hz		
IK Rating: IK04	Electrical Classification: Class I		
IP Rating: IP54	Power Factor: > 0.9		
Beam Angle: 120°	Protection: Overload / Short Circuit		
CRI: > 80	Lifespan: 50,000hrs @Ta25° (L80)		
SDCM: < 5	Operating Ambient Temperature: -20 to 45°C		
Dimming: *Phase-Cut Dimmable			
Smart: KASTA Compatible			
*All the MS models are non-dimmable			

DIMENSIONS (mm)				
250R	300R	350R	400R	400R EM Model

