




# SKYLUX

SKYLUX120W-G2

SAP CODE: 2002090




120W, 0-10V Dimming,  
Wide voltage range,  
Power switchable LED  
High efficacy Highbay

A versatile, cost effective LED  
Highbay for lighting large  
industrial spaces



Photometric  
Diagram



Unit: cd

- C0/180 113.4deg  
- C90/270 113.4deg

## KEY INFORMATION

Lumen Output	11250/12000/15000/18000lm
Input Power	75/80/100/120W
Dimming Options	0-10V Dimming
Trim Colour	BLACK
Warranty	5yr
IP Rating	IP65
IK Rating	IK08

## PHOTOMETRIC

Efficacy	150lm/W
LED	SMD
CCT	5000K
CRI	80
Beam Angle	110°

## ELECTRICAL

Driver	Integral
Supply Input	100-277V, 50/60Hz
Driver Output Voltage	120VDC
Power Factor	>0.9
LED Input Current (nominal)	700-1000mA
Useful life @Ta25° (L70)	50,000hr

## CONSTRUCTION

Housing	Aluminium ADC12
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	1.5m Flex & Plug
Total Weight	3kg
Dimensions	Ø300 x 179mm
Operating Ambient Temp.	-35 to 50°C
Electrical Classification	Class 1