



# STAX LED FLOODLIGHTS

The next generation in outdoor lighting.



# STAX<sup>ECO</sup>

## The next generation in floodlights.

Today's innovative range meets current industry demand for 4000K colour temperature.



### FEATURES

- 4000K CCT
- Power ranges available from 20W to 200W
- Compact designs in low wattage
- IP66 ingress protection rating
- Optional sensor available for selected models
- Optional corner bracket available for all models

### BENEFITS

- Neutral white is more versatile
- Suitable for high power industrial settings
- Suitable for residential settings
- Weather and dust resistant for outdoor use
- Security option for entrance or driveway
- Mount to corner of building for greater coverage

FIND OUT MORE:



PRODUCT CODE	SAP CODE	POWER	LUMEN	CCT	WEIGHT	OPTIONAL ACCESSORIES	
						SENSOR	CORNER BRACKET
STAX20W4K	2002128	20W	1830lm	4000K	0.6kg	✓	✓
STAX30W4K	2002129	30W	2830lm	4000K	0.6kg	✓	✓
STAX100W4K	2002132	100W	9600lm	4000K	1.8kg	N/A	✓
STAX150W4K	2002133	150W	15560lm	4000K	2.4kg	N/A	✓
STAX200W4K	2002134	200W	19560lm	4000K	2.8kg	N/A	✓



50W

15W/30W

# STAX *ECO Multi*

## Multi wattage, Tritone selectable floodlights.

Tritone selectable colour temperature makes these models versatile for a wide range of applications.

-   
**TRITONE**  
Colour Changeable
-   
**IP66**  
Ingress Protection Rating
-   
**IK08**  
Impact Rating
-   
**0-180°**  
Adjustment Angle
-   
**110°**  
Beam Angle
-   
**50,000hr**  
Expected Lifetime
-   
**3yr**  
Warranty

### FEATURES




- Tritone colour selectable
- 6 settings in 1 luminaire (15W/30W)
- IP66 ingress protection rating
- Compact design
- Optional sensor available for 50W model
- Optional corner bracket available for all models

### BENEFITS

- Easily switch between CCT for added versatility
- Extremely versatile for a variety of settings
- Weather and dust resistant for outdoor use
- Suitable for residential settings
- Security option for entrance or driveway
- Mount to corner of building for greater coverage

FIND OUT MORE:



PRODUCT CODE	SAP CODE	POWER	LUMEN	CCT	WEIGHT	OPTIONAL ACCESSORIES	
						SENSOR	CORNER BRACKET
STAX15W30W-TRI	2002130	15W	1720lm 1850lm 1740lm	4000K 5000K 6000K	0.6kg	N/A	
		30W	2710lm 3180lm 2960lm	4000K 5000K 6000K			
STAX50W-TRI	2002131	50W	5330lm 5410lm 4730lm	4000K 5000K 6000K	1.2kg		



# Optional Accessories

## PIR Sensor

**Discreet security lighting.**



Designed to easily fit to selected models and features three easily adjustable sensor settings.

	STAX-SENSOR 2002135	
Compatible Models	STAX20W4K STAX30W4K STAX50W-TRI	
Sensor Type	Passive Infrared	
Detection Angle	120°	
Detection Range	2 - 10m	
Time Setting	10sec - 7min	
Ambient Light	10 - 2000 Lux	

## 90° Bracket

**Designed for extra coverage.**

Allows safe and easy mounting to corners of buildings or square poles for greater light coverage.

	<b>SMALL</b>	<b>LARGE</b>
		
	STAX90D-BRKT-S 2002136	STAX90D-BRKT-L 2002137
Compatible Models	STAX20W4K STAX30W4K STAX15W30W-TRI STAX50W-TRI	STAX100W4K STAX150W4K STAX200W4K



1300 001 LED (533)

[haneco.com.au](http://haneco.com.au)