


# VISTALITE

VSL20W06-TRI-EM

SAP CODE: 2001631




## 20W Tritone indoor LED batten

A diffused appearance LED batten with a choice of 3 colour temperatures.



Photometric Diagram



Unit: cd  
 - C0/180 120.0deg  
 - C90/270 120.0deg

### KEY INFORMATION

Lumen Output	2080 / 2230 / 2120lm
Input Power	20W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	Non-Dimmable
Trim Colour	WHITE
Warranty	4yr
IP Rating	IP40
IK Rating	N/A
IC Rating	N/A
Rebate Scheme Approvals	Pending Approval ETA Mid October

### PHOTOMETRIC

Efficacy	104 / 112 / 106lm/W
LED	SMD
CCT	4000 / 4700 / 5700K
CRI	>80
Beam Angle	120°

### ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	40VDC
Power Factor	>0.9
LED Input Current (nominal)	500mA
Useful life @Ta25° (L70)	50,000hr

### CONSTRUCTION

Housing	Powder Coated Steel
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	N/A
Connection Type	Terminal Block
Total Weight	1.9kg
Dimensions	615 x 68 x 68mm
Operating Ambient Temp.	0 to 45°C
Electrical Classification	Class 1


# Emergency Kit

VISTALITE Emergency with Lithium Iron Phosphate battery technology


VISTALITE emergency batten powered by Lithium Iron Phosphate (LiFePO4) battery technology provides emergency escape lighting during power failures.



Control Gear



Battery



## QUICK FACTS

- Lithium Iron Phosphate (LiFePO4) battery
- Provide emergency lighting during power failures
- Manual testing

## SPECIFICATIONS

Max Battery Temperature	60°
Battery Warranty	2 Years
Operation	Sustained
Emergency Classification	C0 D50 C90 D32

## MAXIMUM SPACING BASED ON 0.2lx (AS/NZS2293.1:2018)

Maximum Spacings Mounting Height (Metres)

Luminaire Classification	2.1	2.4	2.7	3.0	3.3	3.6	4.0	4.5	5.0	6.0	7.0	8.0	9.0	10	15	20
<b>D32</b>	11.5	13.2	14.8	16.5	17.6	18.0	18.5	19.0	19.5	20.1	20.5	20.7	20.6	20.3	0.0	
<b>D50</b>	11.5	13.2	14.8	16.5	18.1	19.8	21.8	22.5	23.1	24.1	24.9	25.4	25.7	25.8	23.6	0.0

