

Weatherproof light fittings and accessories



WS38



616

WS38 series weatherproof single powerpoints, IP33, surface-mounting

Size 73 x 89 x 65mm. Pushouts for 20mm plain conduit at top, sides, rear and bottom. Supplied with 2 x Cat. No. C20S20P connectors for 20mm screwed conduit. Switch padlockable in 'on' or 'off' position. Sealing flush caps provided for cover and mounting screws. Switch is 770 series, socket is 38 series.

Bulkhead weatherproof light fittings, IP33

Mounting centres: 84mm. Size 235 dia x 110mm deep. Suitable for outdoor and wet areas. Surface or wall mounted. 51 & 84mm mounting centres. Terminal block provided. 20mm knockouts in rim, and 20mm & 35mm conduit entry in base. Grey bases available to special order.

| Pack | Cat No. | Description |
|------|---------|--|
| 2 | WS38 | 10A weatherproof single powerpoint |
| 2 | WS38R | 10A weatherproof single powerpoint with round earth |
| 2 | WS38P | 10A weatherproof single powerpoint with double pole switch |

| Pack | Cat No. | Description |
|------|---------|---|
| 1 | 616 | Bulkhead weatherproof BC light fitting. Max lamp 100W. Clear diffuser, white base |
| 1 | 616/1V | Bulkhead weatherproof light fitting, circular 16W energy-saving fluoro tube. White base. (Opal diffuser only - other diffusers not suitable.) |
| 1 | 616DCL | Diffuser only for 616 series. - Clear |



2WS38

2WS38 series weatherproof double powerpoints, IP33, surface-mounting

Size 73 x 123 x 76mm projection. Pushouts for 20mm plain conduit at top, sides, rear and bottom. Supplied with 2 x Cat. No. C20S20P adaptors for 20mm screwed conduit. Switch padlockable in 'on' or 'off' position. Sealing flush caps provided for cover and mounting screws. Switch is 770 series, socket is 38 series.

| Pack | Cat No. | Description |
|------|---------|---|
| 1 | 2WS38 | 10A weatherproof double powerpoint |
| 1 | 2WS38R | 10A weatherproof double powerpoint with round earths |
| 1 | WS38/15 | 15A weatherproof double powerpoint |
| 1 | 2WS38P | 10A weatherproof double powerpoint, with double pole switches |

Weatherproof utility boxes and enclosures



WS45

WS45 series, IP56

For surface mounting. Multi-grid 'gear-tray' accepts #6 self tapping or #6-32 screws. Pushouts for 25mm and 32mm plain conduit entry.

| Pack | Cat No. | Description |
|------|---------|---|
| 1 | WS45 | Utility box, with clear lid (45mm deep) & multi-grid, gear tray |