

# AZURE CEILING FAN



Brushed Chrome no light

**Installation Locations:**

Indoor only

**Standard Canopy Cover:**

Suitable for flat and pitched ceilings up to 32°

**Recommended Height:**

There should be at least 2.1m between the lowest point of the fan blades and the floor.

**Wall Controller Speed Capacitor Values:**

3.5µF & 2µF

**Top of canopy cover to lowest point of the fan without light fittings attached:**

Approximately 350mm

**Rotational Diameter:**

1220mm (48") Blade Sweep

**Motor:**

16 Pole, 153mm x 15mm motor  
Made with the highest grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

**Weight Including Packaging:**

Complete fan 1220mm (48") - 6.6kg

**Packaging Dimensions (cm):**

55.1L x 25.4W x 26.4H

**Motor Housing:**

Materials: Pressed Steel

**Accessories (Supplied separately):**

Remote Control  
Extension Down Rod 21mm diameter (wire harness included)  
T-Hook for ceiling roses

**Available Motor Housing Colours :**

White, Brushed Chrome

**Blades:**

1220mm (48") Straight Style  
Materials: NZ plywood, Painted finish  
Blade Pitch: 12°

**Warranty**

1 year standard warranty "in home" on electronic parts  
2 years standard warranty "in home" on mechanical parts (including motors)  
3 years extended warranty on motor only (excluding labour)

**Available Blade Colours:**

White, Brushed Silver

**Extra Information:**

Introduced into the HPI range in 2016  
3 Speed wall controller  
Reversible

**Airflow and Efficiency:**

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA Energy Star compliance.

| Azure fan 1220mm (48")                                | HIGH       | MED       | LOW       |
|---|------------|-----------|-----------|
| RPMS  | 182        | 145       | 102       |
| WATTS   | 52.4       | 36.3      | 20.9      |
| AIRFLOW: CFM* / CMH*                                  | 6354/10843 | 5061/8637 | 3785/6459 |
| EFFICIENCY <sup>^</sup> : (CFM / Watt) / (CMH / Watt) | 121/207    | 139/238   | 181/309   |

\* CFM = Cubic Feet per Minute / CMH = Cubic Meters per Hour

<sup>^</sup> Efficiency measured as airflow rate per Watt.

# For full warranty details please see Hunter Pacific International's website [www.hunterpacific.com.au](http://www.hunterpacific.com.au)

# AZURE CEILING FAN WITH LIGHT



White motor with light

**Installation Locations:**

Indoor only

**Standard Canopy Cover:**

Suitable for flat and pitched ceilings up to 32°

**Recommended Height:**

There should be at least 2.1m between the lowest point of the fan blades and the floor.

**Wall Controller Speed Capacitor Values:**

3.5µF & 2µF

**Top of canopy cover to lowest point of the fan with light fitting attached:**

Approximately 420mm

**Rotational Diameter:**

1220mm (48") Blade Sweep

**Motor:**

16 Pole, 153mm x 15mm motor  
Made with the highest grade copper windings and silicone steel stator. Bearings are sealed to ensure quiet operation and long life.

**Weight Including Packaging:**

Complete fan 1220mm (48") - 6.9kg

**Packaging Dimensions (cm):**

55.1L x 25.4W x 26.4H

**Available integrated light options:**

Twin E27 screw sockets (bulbs not supplied)

**Motor Housing:**

Materials: Pressed Steel

**Accessories (Supplied separately):**

Remote Control  
Extension Down Rod 21mm diameter (wire harness included)  
T-Hook for ceiling roses

**Available Motor Housing Colours :**

White, Brushed Chrome

**Blades:**

1220mm (48") Straight Style  
Materials: NZ plywood, Painted finish  
Blade Pitch: 12°

**Warranty**

1 year standard warranty "in home" on electronic parts  
2 years standard warranty "in home" on mechanical parts (including motors)  
3 years extended warranty on motor only (excluding labour)

**Available Blade Colours:**

White, Brushed Silver

**Extra Information:**

Introduced into the HPI range in 2016  
3 Speed wall controller  
Only available with light  
Reversible

**Airflow and Efficiency:**

Airflow measured in Australia using the "Energy Star Solid-State Test Method", the only test method recognised for USA Energy Star compliance.

| Azure fan with light 1220mm (48")                     | HIGH       | MED       | LOW       |
|---|------------|-----------|-----------|
| RPMS  | 182        | 145       | 102       |
| WATTS   | 52.4       | 36.3      | 20.9      |
| AIRFLOW: CFM* / CMH*                                  | 6354/10843 | 5061/8637 | 3785/6459 |
| EFFICIENCY <sup>^</sup> : (CFM / Watt) / (CMH / Watt) | 121/207    | 139/238   | 181/309   |

\* CFM = Cubic Feet per Minute / CMH = Cubic Meters per Hour

<sup>^</sup> Efficiency measured as airflow rate per Watt.

# For full warranty details please see Hunter Pacific International's website [www.hunterpacific.com.au](http://www.hunterpacific.com.au)