

# DATA SHEET

## CONDUIT HALF SADDLE

### Attributes:

- Zinc plated, Stainless Steel or hot dip galvanized for strength
- Varied hole size for fixing



	Nominal Diameter (mm)	Hole (mm)	Length (mm)	Width (mm)	Height (mm)	Surface Treatment
KIMCHS12	12.7	5	36	16	15	Zinc plated
KIMCHS16	16	5	46	19	18	Zinc plated
KIMCHS20	20	5	50	19	22	Zinc plated
KIMCHS25	25	5	60	25	26	Zinc plated
KIMCHS32	32	7	67	24	33	Zinc plated
KIMCHS40	40	7	74	32	41	Zinc plated
KIMCHS50	50	7	85	39	54	Zinc plated
KIMCHS20A	20	6.5	50	19	22	Zinc plated
KIMCHS25A	25	6.5	60	25	66	Zinc plated
KIMCHS16HDG	16	5	46	19	18	Hot dip Galvanized
KIMCHS20HDG	20	5	50	19	22	Hot dip Galvanized
KIMCHS25HDG	25	5	60	25	26	Hot dip Galvanized
KIMCHS32HDG	32	7	67	24	33	Hot dip Galvanized
KIMCHS40HDG	40	7	74	32	41	Hot dip Galvanized
KIMCHS50HDG	50	7	85	39	54	Hot dip Galvanized
KIMCHS16SS	16	5	46	19	18	Stainless Steel
KIMCHS20SS	20	5	50	19	22	Stainless Steel
KIMCHS25SS	25	5	60	25	26	Stainless Steel
KIMCHS32SS	32	7	67	24	33	Stainless Steel
KIMCHS40SS	40	7	74	32	41	Stainless Steel