



Data Sheet

LED Satellite



CAT NO. 684850/LI, 684852/LI, 684860/LI, 684862/LI



| Specifications | | |
|-----------------------|--|----------------------|
| Cat No | 684850/LI, 684852/LI | 684860/LI, 684862/LI |
| Type | SPU | AXIOM |
| Lamp | 1x2W LED | |
| Battery pack | Li-ion 6.4V, 1.5Ah with PCM-B | |
| Operating Voltage | 240V a.c. +/- 6% 50Hz | |
| Power Consumption | 0.95W | 1.4W |
| Body Constructions | Polycarbonate | |
| Operating Temperature | 10° to 40° | |
| IP Rating | IP20 | |
| Compliance | AS/NZS 2293 AS/NZS 60598   | |

LED Satellite

CAT NO. 684850/LI, 684852/LI, 684860/LI, 684862/LI



- Suitable for all emergency lighting applications
- Energy efficient: less than 1W energy consumption in stand by mode (SPU)
- Easy to install
- Suitable for different hole sizes
- iSmart™ temperature sensing technology for LIION battery
- Electronics designed to lengthen the life of the battery
- SPU or Axiom options
- Also available in black
- 5 year warranty
- Manufactured in Australia

| Cat No | Description | Classification C ₀ /C ₉₀ |
|--------------|---|--|
| SPU | | |
| 684850/LI | Satellite LED 1x02W Flex and Plug | D40 |
| 684852/LI | Satellite LED 1x02W Flex and Plug Black | D40 |
| Axiom | | |
| 684860/LI | Axiom Satellite LED 1x02W Flex and Plug | D40 |
| 684862/LI | Axiom Satellite LED 1x02W Flex and Plug Black | D40 |

| Dish sizes | Dish diameter | Hole cut-out | Recommended hole cut out |
|--------------------|---------------|---------------|--------------------------|
| Extra small | 56mmØ | 52mmØ | 52mmØ |
| Small | 80mmØ | 52mm - 60mmØ | 55mmØ |
| Medium | 120mmØ | 52mm - 85mmØ | 75mmØ |
| Large | 150mmØ | 75mm - 125mmØ | 120mmØ |

Legrand - Australia
1300 369 777
www.legrand.com.au
ABN 31 000 102 661

Legrand - New Zealand
0800 476 009
www.legrand.co.nz

Refer to your group buying office, Legrand Sales Representative or
Legrand Sales Office for pricing.

Please note: specifications are subject to change without prior notice.