



# FLOAT SWITCH - 9010 SERIES




- **Liquid Temperature:** Min 5° C (32° F)  
Max 60° C (140° F)
- **Liquid Density:** Min .65g/cm  
Max 1.5g/cm
- **Protection:** IP68 @ 20m (65ft)
- **Working Pressure:** .35MPa
- **Switching Speed:** 600/min
- **Contact Life:** 10,000 switches
- **Contact Type:** Microswitch with NO and NC contacts
- **Switching Angle:** 20° (from horizontal)
- **Max Voltage:** 240Vac
- **Max Current:** 6AMPS (COS 0)
- **Cable Material:** Neoprene Rubber
- **Cable Size:** ø7mm / 3 x .75mm<sup>2</sup>
- **Housing Material:** ABS - Acrylonine Butadiene Styrene
- **Chemical Resistance:** Acid - Good  
Alkaline - Good  
Petro - Good



Close on Fall - (Normally Closed)



Close on Rise



Dimensions

Code	Description	Packing	MOQ	Ctn
FSW-12517	9010 NRB 10m Cable	1	1	10
FSW-12518	9010 NRB 15m Cable	1	1	10
FSW-12519	9010 NRB 20m Cable	1	1	10
FSW-12520	9010 NRB 30m Cable	1	1	5
FSW-12521	9010 NRB 40m Cable	1	1	5