

MT723 Clamp Meter

The MT723 is a CAT III 600V, 4000 count True RMS 400A AC/DC digital clamp meter with indication on a large backlit LCD display, providing fast sampling time with high accuracy. The meter measures 1000V AC/DC, temperature, frequency, capacitance and resistance measurements, plus 100ms Inrush current and Peak Voltage value. The VFD function allows the user to measure stable voltage in high frequency applications of Variable Frequency Drives. Added features include Relative mode for Capacitance Zero and DCV, ACV and ACA offset adjustment, Non-Contact voltage detection, data hold function and a built-in flashlight for dimly lit areas. Housed in a modern double moulded rubber housing.





1000V

IEC

61010-1

CAT III

Features

- 4000 count backlit LCD display
- Ø30mm Cable Clamp size
- Measurement of DC voltage and AC voltage up to 1000V
- Capacitance to 100mF
- Temperature measurement from -20°C to 1000°C
- **INRUSH Current Measurements**
- VFD Variable Frequency Drive voltage value
- NCV Non-Contact Voltage Detector
- Built-In Flashlight
- Continuity buzzer and Diode Test
- Peak Mode and Data Hold function
- Auto Power Off

Function	Range	Accuracy
DC Current	40.00A - 400A	±(2.0% +8)
AC Current	40.00A - 400A	±(2.0% +8)
DC Voltage	4.000V - 1000V	±(1.0% +3)
AC Voltage	4.000V - 1000V	±(1.2% +5)
Resistance	400.0Ω - 40ΜΩ	±(1.5% +2)
Frequency	10Hz – 100kHz	±(1.0% +5)
Capacitance	99.00nF – 100mF	±(3.0% +5)
Temperature	-20°C — 1000°C	±(3.0%+3°C)
Duty Cycle	20.0% to 80%	±(1.2% +10)
Size	220 x 80 x 39mm	
Weight	305g	



Red Light indicates detection of Non Contact Voltage (NCV)



4000 Count Backlit **LCD Display**



Rear entry of standard **4mm Test Lead Terminals**



Inrush Current, Peak Hold & VFD Measurements



Meter includes flash light to light up area of test

MT723

400A AC Clamp Meter

Contact Us **South Africa**





