



DATA SHEET:

MEDIUM DUTY CORRUGATED CONDUIT (MD)

Australian made by an Australian owned company, Aussie Duct medium duty corrugated conduit is suitable for indoor or outdoor installations. Manufactured to Australian standard AS/NZS2053 and conforms with "Best Practice Guidelines for PVC in the Built Environment" (Green Star). We also manufacture a range of conduit fittings for our medium duty corrugated conduit.


TECHNICAL SPECIFICATION	
MATERIAL	PVC-U
COLOUR	GREY
DUTY RATING	MEDIUM
PRODUCT STANDARD	AS/NZS2053.2
UV RESISTANT	YES—UV (T) STABILISED
B.E.P CERTIFIED	YES (CERTIFICATE: 4008)
TEMPERATURE RANGE	0-60°C
COMPRESSION RESISTANCE	750N/5cm
DIELECTRIC STRENGTH	ELECTRO-INSULATING
FLAME PROPAGATION	Non-flame Propagating
QUALITY MANAGEMENT SYSTEM	ISO9001:2015 (CERTIFICATE: QEC0597)



100%AussieMade







Product Code	Size	Coil Length (L)	Nominal Size (ØA)	Pack Qty	Pallet Qty	Draw Wire
MC16GR	16mm	10m	16mm	1	90	
CC16GR	16mm	50m	16mm	1	35	
MC20GR	20mm	10m	20mm	1	90	
SH20GR20M	20mm	20m	20mm	1	81	
CC20GR	20mm	50m	20mm	1	30	
CC2020GR	20mm	50m	20mm	1	30	✓
MC25GR	25mm	10m	25mm	1	54	
SH25GR20M	25mm	20m	25mm	1	54	
CC25GR	25mm	50m	25mm	1	25	
CC2025GR	25mm	50m	25mm	1	25	✓
MC32GR	32mm	10m	32mm	1	50	
CC32GR	32mm	25m	32mm	1	25	
MC40GR	40mm	10m	40mm	1	24	
CC40GR	40mm	25m	40mm	1	20	
MC50GR	50mm	10m	50mm	1	20	
CC50GR	50mm	25m	50mm	1	10	