



Representative Photo Only
(actual product may vary based on configuration selections)

CSB flush mount loadcentre, 24way, white door

- IP40 rating
- Split neutral and earth bars rated 100A
- Removable earth and neutral bar
- White or transparent door
- Door hinged at the top
- Supplied complete with busbar comb
- Base (ABS)
- Door (white -ABS), (transparent (polycarbonate)
- 8way- Neutral split 4/4 & 8way earth, 12way- Neutral split 5/3/3 & 12way earth
- 18way- Neutral split 9/3/3/3 & 18way earth, 24way- Neutral split 10/3/3/3/3 & 24way earth
- 36way- Neutral split 12/12/12 & 36way earth

SPECIFICATIONS

Product Series	CSB
Component Type Power Distribution & Protection	Loadcentre Enclosure
IP Rating	IP40
Number of Poles	24
MCB Type	DIN Profile
Material, Body / Housing	ABS material
Colour, Body / Housing	White colour
Material, door	White-ABS, Clear PC (PolyCarbonate)
Colour, Door	White door
Ue, rated operational voltage, AC, 3ph, nom	415 V AC
Ue, rated operational voltage, AC, 1ph, nom	240 V AC
In, Rated Current	100 A
In, rated current, busbar comb, centre feed	130 A
In, rated current, busbar comb, end feed	80 A
Tunnels, neutral bar	10/3/3/3/3
Tunnels, earth bar	24
Mounting	Flush Mount
Height	358 mm
Width	305 mm
Depth	105 mm
Height, base	304 mm
Width, base	270 mm
Depth, Base	76 mm
Height, cover	358 mm
Width, cover	305 mm
Depth, cover	29 mm
Height, Cutout	311 mm
Width, Cutout	259 mm

Catalogue No: **CSB24FW**

LOADCENTRE 24 WAY DIN FLUSH WHITE DOOR

Power Distribution and Protection > Distribution Boards > Loadcentre Assemblies > MOD6 Range of Loadcentres > MOD6 CSB Loadcentres > Insulated Flush Mount White Door



Earth and Neutral bar Rating 100 A 16 mm tunnel terminals

Standards Compliance AS/NZS 3439.3

REFERENCES

IECEX Certificate -

Supplier Declaration of Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue & Product Selection: -

