



Representative Photo Only
(actual product may vary based on configuration selections)

**Enclosure Wall Mount N-Line Mild Steel IP66
H200xW200xD155mm**

- 14 sizes in RAL 7035 light grey powder coating, with IP66 and IK10 protection ensuring a good quality product.
- Includes 2mm galvanised steel mounting plate, gland plate, quarter turn double-bit 3mm insulated lock and key providing all you need for installation straight away
- Reversible door allows for flexibility in installation with the same enclosure able to be used in double the applications
- Recommended for indoor use only.

SPECIFICATIONS

Product Series	NLS
Material, Body / Housing	Powder Coated Mild Steel material
Colour, Body / Housing	Light Grey (RAL 7035) colour
Finish, body / housing	Ripple body/housing
Height	200 mm
Width	200 mm
Depth	155 mm
Weight	3 kg
IP Rating	IP66
IK Rating	IK10
Material, Mounting Plate / Bracket	Zinc Galvanized Steel
Material Thickness, Mounting Plate / Bracket	2 mm
Height, Mounting Plate	170 mm
Width, Mounting Plate	150 mm
Number of Gland Plates	1 qty
Height, Gland Plate Opening	110 mm opening height
Width, Gland Plate Opening	56 mm opening width
Number of Locks	1 qty
Lock Type	DIN - 1/4 Turn type
Diameter, Lock	3 mm
Material, Lock	Plastic material
Certifications	CE

Catalogue No: **NLS0202015**

ENCLOSURE W/MOUNT N-LINE M/STEEL IP66 H200 x W200 x D155mm

Enclosures and Climate Control > Standard Enclosures > Wall Mount Enclosures > N-Line Wall Mount Enclosures - Mild Steel > Wall Mount Enclosures - Nline



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -