


Eco Batten Emergency Gen4

The Pierlite Eco LED Batten Gen4 is a one box solution with Colour and Lumen select feature. The quick release clips, removable connector and sealed LED module makes it easy to install and maintain. With up to 110lm/W, the efficacy makes it an ideal replacement for traditional fluorescent battens.



- Up to 120lm/W efficiency.
- Clean and uniform opal diffuser for even light distribution
- Lumen select 2ft(11W to 18W) and 4ft(18W to 36W). Colour Select (4000K, 5000K, 6500K)

LUMEN SELECT COLOUR SELECT

80	IP20	5SDCM	0 to 40	Non - Dimmable	5 Years	Symmetric	120°
CRI	Ingress Protection Rating	MacAdam Steps	Operating Temperature	Dimming	Warranty	Beam Distribution	Beam Angle

CODE	SYSTEM POWER	EXIT LUMEN	EFFICACY	CCT	DIMENSIONS	WEIGHT	INRUSH CURRENT	CLASSIFICATION
ECOBAT202ECSLSG 4M	18W	1900lm	120lm/W	4000K	L603 x W74 x H74 mm	0.80kg	14A	C0/C180: D40 & C90/C270: D25
	16W	1600lm		5000K				
	14W	1400lm		6500K				
	11W	1100lm						
ECOBAT404ECSLSG 4M	25W	3000lm	120lm/W	4000K	L1164 x W74 x H74 mm	1.5kg	17A	C0/C180: D50 & C90/C270: D25
	30W	3500lm		5000K				
	36W	4000lm		6500K				
	18W	2300lm						

EMERGENCY MODE WATTAGE	OPTION	BATTERY	BATTERY CHARGE	BATTERY VOLTAGE	BATTERY CAPACITY	TESTING SYSTEM
3W	Maintained	LiFePO4	2hr	6.4V	1500mA	Manual



AS/NZS 2293.1:2018 Classification Table

ECOBAT202ECSLSG4M C0/C180: D40 & C90/C270: D25			
Allowable Luminaire Mounting Height (m)	Luminaire Maximum Spacing for each Plane (M)		
	C0	C90 / C270	C180
2.1	11.5	11.5	11.5
2.4	13.2	13.2	13.2
2.7	14.8	14.8	14.8
3	16.5	15.7	16.5
3.3	18.1	16.1	18.1
3.6	19.8	16.4	19.8
4	21.8	16.8	21.8
4.5	22.5	17.3	22.5
5	23.1	17.6	23.1
6	24.1	18.1	24.1
7	24.9	18.3	24.9
8	25.4	18.2	25.4

ECOBAT202ECSLSG4M

ECOBAT404ECSLSG4M C0/C180: D50 & C90/C270: D25			
Allowable Luminaire Mounting Height (m)	Luminaire Maximum Spacing for each Plane (M)		
	C0	C90 / C270	C180
2.1	11.5	11.5	11.5
2.4	13.2	13.2	13.2
2.7	14.8	14.8	14.8
3	16.5	15.7	16.5
3.3	18.1	16.1	18.1
3.6	19.8	16.4	19.8
4	21.8	16.8	21.8
4.5	22.5	17.3	22.5
5	23.1	17.6	23.1
6	24.1	18.1	24.1
7	24.9	18.3	24.9
8	25.4	18.2	25.4

ECOBAT404ECSLSG4M



ECOBAT202ECSLSG4M

ECOBAT404ECSLSG4M

Product Images

