

Shadoweco LED Floodlight

SHADOWECO100BK

- Black Powder coated die-cast Aluminium LM6 Body profile with excellent heat sink capability
- Textured tempered glass to minimize glaze, 316 grade stainless steel screws
- Hassle-free with pre-wired 1 meter flying lead and angled Trunnion arm for easy installation



Performance

System Power	100W
Exit Lumen	10000lm
Lm/W	100lm/W
CCT	4000K
CRI	80
Operating Temperature	0 - 40°C
MacAdam Steps	6SDCM
Ingress Protection Rating	IP65
Impact Rating	IK08
Beam Distribution	Symmetric
Beam Angle	110°
Warranty	3 Years
Lifetime	50,000hrs (L70/B50)


Physical

Dimensions	L339 x W322 x H98mm
Reflector	Aluminium
Diffuser	Frosted Glass
Luminaire Colour	Black
Weight	4kg
Luminaire Material	Aluminium (Die Cast)
Driver Location	Integrated
Heatsink	Aluminium (Die Cast)
Finish	Powder Coated
Installation	Trunnion

Electrical

Dimming	Non - Dimmable
Voltage	240V
Inrush Current	4A
Line Current	0.46A
Electrical Rating	Class 1

Line Drawings



Product Images



