




LIFESAVER

6000 SERIES

6000DCW SMOKE ALARM

10 Year Lithium Battery (non-replaceable) with Wireless RF Interlink



Tested & Complies to
Australian Standards
AS3786:2014

Application

The PSA Lifesaver 6000DCW model is a 10 year lithium battery powered smoke alarm with an in-built wireless RF interlink. It is designed to be interlinked with other 6000DCW units & Lifesaver 6000 series smoke alarms fitted with a 6000WB base.

When paired with the 6000THL (wireless smoke alarm controller), the 6000DCW smoke alarm can be operated via remote control, offering effortless test/hush functionality.

The alarm uses photoelectric technology is designed to be surface mounted on the ceiling or wall. 6000DCW can be used as a single stand alone unit, or be interconnected with up to 24 units.

Features

- Wireless, surface mount smoke alarm
- Powered by 10 year lithium battery (non-replaceable)
- Photoelectric sensing technology
- Compatible with 6000THL smoke alarm controller, and 6000 series alarms fitted with 6000WB wireless base
- Easy power on / power off baseplate
- Wirelessly interconnect up to 24 units
- Bug screen sensor chamber protection (0.8mm Ø)
- Electronics coating to prevent build up of heat and condensation caused by humidity and high temperatures
- Sensor interference filter technology to reduce false alarms
- Anti-static chamber to repel dust and reduce false alarms
- Single button test and hush feature, with low battery hush
- Fully supervised, secured and monitored wireless RF network
- 10 year warranty
- ActivFire certified, AS3786:2014, AS4268:2017



6000DCW SMOKE ALARM

10 Year Lithium Battery (non-replaceable) with Wireless RF Interlink

Technical Specifications

Model	6000DCW
Part Number	LIF6000DCW
Sensor Type	Photoelectric
Smoke Alarm Power	Panasonic/FDK 10year 3VDC CR17335 fixed battery (non-replaceable)
RF Power	Panasonic/FDK 10year 3VDC CR17455 fixed battery (non-replaceable)
Interconnecting	Interconnectable up to 24 units
Alarm Volume	85dBA at 3 metres
Alarm Signal Pattern	ISO8201 (T3 - Repeat 3 long beeps)
Temperature Range	0°C - 40°C
Humidity Range	Up to 95% RH (non-condensing)
RF Frequency	918MHz
RF Range	100m line of sight 30m indoors
Hush Function	Silences alarm for 10 minutes Red LED flashes every 10 seconds Dense smoke will override hush function
Alarm Duration	Alarm will sound for as long as smoke is detected, then unit will automatically reset when smoke clears.
Alarm Indication	Red LED flashes every second. For interconnected, only the red LED of initiating unit will flash.
Chamber Monitoring	Red LED flashes 10 times and chirps every 30 seconds. Indicates maintenance is required.
Indicator LEDs	Red LED - Alarm status indicator, differentiated by frequency of flashes.
Approvals	ActivFire RCM AS3786:2014 AS4268:2017
Warranty	10 years

Product

LIF6000DCW	Quantity	Barcode
Single	1	9318475001806
Pack	6	19318475001803
Carton	24	29318475001800

Compatibility

6000THL	Smoke alarm control (wireless)
6000WB	Wireless baseplate
6000	240V, 9V battery backup smoke alarm (requires 6000WB)
6000RL	240V, 10yr backup battery smoke alarm (non-replaceable) (requires 6000WB)

Accessories

LIFHA240	Heat alarm with 9V battery backup
LIFCO240	Carbon monoxide alarm
LIFLT711	Smoke alarm tester (aerosol)

Due to continual product development, PSA Products Pty Ltd reserves the right to alter specifications, product details, modify designs and discontinue items without notice or incurring obligation. Whilst every effort is made to ensure that specifications and other information in this document are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein. © 2021 PSA Products Pty Ltd. All Rights Reserved.

