



LIFESAVER

MODEL **LIFPE9M**


9V PHOTOELECTRIC

SMOKE ALARM



FEATURES:

- Photoelectric sensor
- Slim-line compact size
- Red led light for alarm indication and testing
- Mute button to silence nuisance alarms
- Alarm test button
- Low battery warning signal
- Mounting screws supplied
- Easy twist on twist off installation
- Complies & Approved to Australian Standard AS3786:2014
- Loud 85db alarm



120mm mounting plate available.
Part no. LIFSAplate



Tested & complies to
Australian Standards
AS3786:2014



Excludes battery

SPECIFICATION:

Power Source	9V Battery
Battery Type	Gold Peak 1604A. Gold Peak 1604S
Operating Temp	0°C to 45°C
Ambient Humidity	10%-90%
Alarm Sound Level	85 Decibels at 3 metres ISO8201 pattern.
Battery Life	1 year minimum
Detection Method	Photoelectric sensor
Low battery indication	Chirps when battery needs replacing
Alarm duration	As long as smoke is present, resets when smoke clears.
Mute mode	When in Mute mode, the unit is desensitized for 10 minutes.
Mute indication	Red LED flash every 8 seconds for 10 minutes, then resets.
Tested & Passed to	AS3786-2014
Dimensions	90mm diameter x 35mm high, 120mm mounting plate available

FIRE • SECURITY • INTERCOMS

1300 772 776 enquiry@psaproducts.com.au
psaproducts.com.au

