

Product data sheet

Characteristics

A9D11216

Acti9, Residual current breaker with overcurrent protection (RCBO), Acti9 iC60H2 RCBO, 2P, 16A, 30mA, A type, 10000A



Main

| | |
|-----------------------------|---|
| Circuit breaker application | Distribution |
| Range | Acti9 |
| Product name | Acti9 iC60 RCBO |
| Product or component type | Residual current breaker with overcurrent protection (RCBO) |
| Device short name | IC60H2 RCBO |
| Poles description | 2P |
| [In] rated current | 16 A at 50 °C |
| Earthing system | TN TT IT |
| Curve code | C |
| Earth-leakage sensitivity | 30 mA |
| Breaking capacity | 10000 A Icn at 230/240 V AC 50/60 Hz |

Complementary

| | |
|--|---|
| Neutral position | Left |
| Number of protected poles | 2 |
| Device location in system | Outgoer |
| Network frequency | 50 Hz |
| Network type | AC |
| Trip unit technology | Thermal-magnetic |
| [Ue] rated operational voltage | 230/240 V AC 50/60 Hz |
| Residual current tripping technology | Voltage dependent |
| Earth-leakage protection time delay | Instantaneous |
| Earth-leakage protection class | Type A |
| [Icw] rated short-time withstand current | Icw: 250 A during 8/20 μs impulse withstand |
| [Ics] rated service breaking capacity | 7500 A at 230/240 V AC 50/60 Hz |
| Limitation class | 3 |
| [Ui] rated insulation voltage | 400 V AC 50/60 Hz |
| [Uimp] rated impulse withstand voltage | 4 kV |
| Surge current | 250 A |
| Suitability for isolation | Yes |
| Contact position indicator | Yes |
| Control type | Toggle |
| Local signalling | ON/OFF indication |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| Comb busbar and distribution block compatibility | NO |
| 9 mm pitches | 4 |
| Height | 110 mm |
| Width | 36 mm |
| Depth | 75.5 mm |

| | |
|-----------------------------|--|
| Net weight | 332 g |
| Colour | White |
| Mechanical durability | 20000 cycles |
| Electrical durability | 5000 cycles |
| Provision for padlocking | Padlockable with padlock Ø 4 mm |
| Locking options description | ON/OFF locking facilities |
| Connections - terminals | Screw clamp terminal (top) 1...25 mm ² rigid without cable end Screw clamp terminal (top) 1...16 mm ² flexible Screw clamp terminal (bottom) 1...16 mm ² rigid without cable end Screw clamp terminal (bottom) 1...10 mm ² flexible |
| Wire stripping length | Power circuit: 13 mm for bottom connection Power circuit: 14 mm for top connection |
| Tightening torque | Power circuit: 3.5 N.m top Power circuit: 2 N.m bottom |
| Earth-leakage protection | Integrated |

Environment


| | |
|---------------------------------------|--|
| Standards | IEC 61009-1 IEC 61009-2-2 AS/NZS 61009.1 |
| IP degree of protection | IP20 |
| Tropicalisation | 2 |
| Relative humidity | 95 % at 55 °C |
| Ambient air temperature for operation | -15...60 °C |
| Ambient air temperature for storage | -40...85 °C |

Packing Units

| | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 13.6 cm |
| Package 1 Width | 4.4 cm |
| Package 1 Length | 9.2 cm |
| Package 1 Weight | 306.0 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 27 |
| Package 2 Height | 15.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 8.668 kg |
| Unit Type of Package 3 | P12 |
| Number of Units in Package 3 | 864 |
| Package 3 Height | 70.0 cm |
| Package 3 Width | 120.0 cm |
| Package 3 Length | 80.0 cm |
| Package 3 Weight | 276.384 kg |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| Sustainable packaging | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |

| | |
|-----------------------------|---|
| Circularity Profile |  End Of Life Information |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Halogen content performance | Halogen free plastic parts product |
