



Main

Range	Acti 9
Product or component type	Distribution board
Device application	Distribution
Colour	White (RAL 9003)
Provided equipment	Enclosure Earthing bar Pan assembly Removable gland plates at top and bottom of the enclosure Isolator Neutral bar
Door type	Plain

Complementary

Enclosure mounting	Surface
Protection device type	Main incomer: isolator - 160 A Outgoer: miniature circuit breaker (MCB) - 63 A Outgoer: residual current circuit breaker with overcurrent protection (RCBO) - 63 A
[Ie] rated operational current	160 A at 240/415 V AC
[Icw] rated short-time withstand current	25 kA for 100 ms
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Number of ways	54 ways
Enclosure/Cubicle description	Single door enclosure
Height	1078 mm external:
Width	470 mm external:
Depth	140 mm external:
Net weight	26.5 kg

Environment

Ambient air temperature for operation	-15...50 °C
IP degree of protection	IP40
Standards	AS/NZS 61439-3

Packing Units

Package 1 Weight	26.500 kg
Package 1 Height	10.890 dm
Package 1 width	4.800 dm
Package 1 Length	1.500 dm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information