

# Product datasheet

Specifications

## Attached Cable T2 16A 3-Ph IEC 4 meters - Wallbox EVH2 spare part



EVP2CNS163C4

### Main

|                                    |   |
|------------------------------------|---|
| Range                              | EVlink  |
| Product Or Component Type          | Charging cable  |
| Accessory / Separate Part Category | Spare part  |
| Network Number Of Phases           | Three phase   |
| Poles Description                  | 3P + N  |
| [In] Rated Current                 | 16 A  |
| [Us] Rated Supply Voltage          | 380...415 V AC 50/60 Hz   |
| Earthing System                    | Compatible TN<br>Compatible IT with additional isolation transformer on the power supply<br>Compatible TT |
| Nominal Output Power               | 11 W 16 A   |
| Socket Number                      | 1   |

### Complementary

|                        |   |
|------------------------|---|
| Connector Type         | T2 vehicle end silver plated contacts<br>Without connector charging station end |
| Range Compatibility    | EVlink EVlink Wallbox EVH2 charging station                                     |
| Standards              | IEC 62196-2<br>IEC 62196-1  |
| Product Certifications | CE  |
| Length                 | 4 m   |
| Net Weight             | 3.1 kg  |

### Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Ip Degree Of Protection               | IP54 conforming to IEC 60529 |
| Ik Degree Of Protection               | IK10 conforming to IEC 62262 |
| Ambient Air Temperature For Operation | -30...50 °C                  |
| Ambient Air Temperature For Storage   | -40...80 °C                  |
| Relative Humidity                     | 5...95 %                     |

### Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type Of Package 1       | PCE |
| Number Of Units In Package 1 | 1   |

|                                     |          |
|-------------------------------------|----------|
| <b>Package 1 Height</b>             | 15 cm    |
| <b>Package 1 Width</b>              | 30 cm    |
| <b>Package 1 Length</b>             | 40 cm    |
| <b>Package 1 Weight</b>             | 1.582 kg |
| <b>Unit Type Of Package 2</b>       | S02      |
| <b>Number Of Units In Package 2</b> | 1        |
| <b>Package 2 Height</b>             | 15 cm    |
| <b>Package 2 Width</b>              | 30 cm    |
| <b>Package 2 Length</b>             | 40 cm    |
| <b>Package 2 Weight</b>             | 2.037 kg |

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance

✓ Reach Free Of Svhc

---

✓ Toxic Heavy Metal Free

---

✓ Mercury Free

---

✓ Rohs Exemption Information [Yes](#)

---

**Reach Regulation** [REACH Declaration](#)

---

**Eu Rohs Directive** [Compliant](#)  
[EU RoHS Declaration](#)

---

**China Rohs Regulation** [China RoHS declaration](#)

---