

Product data sheet

Characteristics

EY56SW332

Easy56, Switch, 3P, 32A, 500V



Main

Product name	Easy56
Device short name	EY56SW332
Product or component type	Switch
Poles description	3P
Control type	Rotary knob
Rotary handle padlocking	2 padlocks 8 mm

Complementary

[Ue] rated operational voltage	500 V AC 50 Hz
[Uimp] rated impulse withstand voltage	2.5 kV conforming to IEC 60947-3 2.5 kV conforming to AS/NZS 3133
[Ithe] conventional enclosed thermal current	32 A
[Ie] rated operational current	32 A (AC-21A) at 500 V AC 32 A (AC-23A) at 500 V AC
Making capacity	320 A at 500 V AC-21A 320 A at 500 V AC-23A
[Icm] rated short-circuit making capacity	1 kA at 500 V AC-21A 1 kA at 500 V AC-23A
[Icw] rated short-time withstand current	1.5 kA at 500 V duration: 1 s
Breaking capacity	0.2 kA at 500 V (AC-21A) 0.2 kA at 500 V (AC-23A)
Suitability for isolation	Yes
Connections - terminals	Screw terminals cable(s) 1...16 mm ² rigid or stranded
Height	101 mm
Width	101 mm
Depth	101 mm
Net weight	0.471 kg
Colour	Body: grey (RAL 7035) Rotary handle: dark grey

Environment

Standards	AS/NZS 3133
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-25...75 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.6 cm
Package 1 Width	10.8 cm
Package 1 Length	10.9 cm
Package 1 Weight	510.0 g

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes