



## Main

|                                |  |
|--------------------------------|--|
| Range                          | TeSys<br>TeSys Deca  |
| Range of product               | TeSys Deca   |
| Product or component type      | Contacteur   |
| Device short name              | LC1D   |
| Contacteur application         | Motor control<br>Resistive load  |
| Utilisation category           | AC-4<br>AC-1<br>AC-3<br>AC-3e  |
| Poles description              | 3P   |
| [Ue] rated operational voltage | Power circuit: ≤ 690 V AC 25...400 Hz<br>Power circuit: ≤ 300 V DC   |
| [Ie] rated operational current | 60 A (at <60 °C) at ≤ 440 V AC AC-1 for power circuit<br>40 A (at <60 °C) at ≤ 440 V AC AC-3 for power circuit<br>40 A (at <60 °C) at ≤ 440 V AC AC-3e for power circuit |
| [Uc] control circuit voltage   | 240 V AC 50/60 Hz  |

## Complementary

|                          |   |
|--------------------------|---|
| Motor power kW           | 18.5 kW at 380...400 V AC 50/60 Hz (AC-3)<br>11 kW at 220...230 V AC 50/60 Hz (AC-3)<br>22 kW at 415...440 V AC 50/60 Hz (AC-3)<br>22 kW at 500 V AC 50/60 Hz (AC-3)<br>30 kW at 660...690 V AC 50/60 Hz (AC-3)<br>9 kW at 400 V AC 50/60 Hz (AC-4)<br>18.5 kW at 380...400 V AC 50/60 Hz (AC-3e)<br>11 kW at 220...230 V AC 50/60 Hz (AC-3e)<br>22 kW at 415...440 V AC 50/60 Hz (AC-3e)<br>22 kW at 500 V AC 50/60 Hz (AC-3e)<br>30 kW at 660...690 V AC 50/60 Hz (AC-3e) |
| Motor power hp           | 5 Hp at 230/240 V AC 50/60 Hz for 1 phase motors<br>10 Hp at 230/240 V AC 50/60 Hz for 3 phases motors<br>30 Hp at 575/600 V AC 50/60 Hz for 3 phases motors<br>10 Hp at 200/208 V AC 50/60 Hz for 3 phases motors<br>3 Hp at 115 V AC 50/60 Hz for 1 phase motors<br>30 Hp at 460/480 V AC 50/60 Hz for 3 phases motors  |
| Compatibility code       | LC1D  |
| Pole contact composition | 3 NO  |
| Contact compatibility    | M2  |
| Protective cover         | With  |

|   |   |
|---|---|
| [Ith] conventional free air thermal current | 10 A (at 60 °C) for signalling circuit<br>60 A (at 60 °C) for power circuit   |
| Irms rated making capacity                  | 140 A AC for signalling circuit conforming to IEC 60947-5-1<br>250 A DC for signalling circuit conforming to IEC 60947-5-1<br>800 A at 440 V for power circuit conforming to IEC 60947  |
| Rated breaking capacity                     | 800 A at 440 V for power circuit conforming to IEC 60947  |
| [Icw] rated short-time withstand current    | 320 A 40 °C - 10 s for power circuit<br>720 A 40 °C - 1 s for power circuit<br>72 A 40 °C - 10 min for power circuit<br>165 A 40 °C - 1 min for power circuit<br>100 A - 1 s for signalling circuit<br>120 A - 500 ms for signalling circuit<br>140 A - 100 ms for signalling circuit |
| Associated fuse rating                      | 10 A gG for signalling circuit conforming to IEC 60947-5-1<br>80 A gG at <= 690 V coordination type 1 for power circuit<br>80 A gG at <= 690 V coordination type 2 for power circuit  |
| Average impedance                           | 1.5 MOhm - Ith 60 A 50 Hz for power circuit   |
| Power dissipation per pole                  | 2.4 W AC-3<br>5.4 W AC-1<br>2.4 W AC-3e   |
| [Ui] rated insulation voltage               | Power circuit: 600 V CSA certified<br>Power circuit: 600 V UL certified<br>Signalling circuit: 690 V conforming to IEC 60947-1<br>Signalling circuit: 600 V CSA certified<br>Signalling circuit: 600 V UL certified<br>Power circuit: 690 V conforming to IEC 60947-4-1               |
| Overvoltage category                        | III   |
| Pollution degree                            | 3   |
| [Uimp] rated impulse withstand voltage      | 6 KV conforming to IEC 60947  |
| Safety reliability level                    | B10d = 1369863 cycles contactor with nominal load conforming-<br>to EN/ISO 13849-1<br>B10d = 20000000 cycles contactor with mechanical load conforming-<br>to EN/ISO 13849-1  |
| Mechanical durability                       | 6 Mcycles   |
| Electrical durability                       | 1.4 Mcycles 60 A AC-1 at Ue <= 440 V<br>1.5 Mcycles 40 A AC-3 at Ue <= 440 V<br>1.5 Mcycles 40 A AC-3e at Ue <= 440 V   |
| Control circuit type                        | AC at 50/60 Hz  |
| Coil technology                             | Without built-in suppressor module  |
| Control circuit voltage limits              | 0.3...0.6 Uc (-40...70 °C):drop-out AC 50/60 Hz<br>0.8...1.1 Uc (-40...60 °C):operational AC 50 Hz<br>0.85...1.1 Uc (-40...60 °C):operational AC 60 Hz<br>1...1.1 Uc (60...70 °C):operational AC 50/60 Hz   |
| Inrush power in VA                          | 140 VA 60 Hz cos phi 0.75 (at 20 °C)<br>160 VA 50 Hz cos phi 0.75 (at 20 °C)  |
| Hold-in power consumption in VA             | 13 VA 60 Hz cos phi 0.3 (at 20 °C)<br>15 VA 50 Hz cos phi 0.3 (at 20 °C)  |
| Heat dissipation                            | 4...5 W at 50/60 Hz   |
| Operating time                              | 4...19 ms opening<br>12...26 ms closing   |
| Maximum operating rate                      | 3600 Cyc/H 60 °C  |

|                               |   |
|-------------------------------|---|
| Connections - terminals       | <p>Control circuit: screw clamp terminals 2 1...2.5 mm<sup>2</sup> - cable stiffness: flexible with-cable end</p> <p>Control circuit: screw clamp terminals 1 1...4 mm<sup>2</sup> - cable stiffness: flexible without cable end</p> <p>Control circuit: screw clamp terminals 2 1...4 mm<sup>2</sup> - cable stiffness: flexible without cable end</p> <p>Control circuit: screw clamp terminals 1 1...4 mm<sup>2</sup> - cable stiffness: flexible with-cable end</p> <p>Control circuit: screw clamp terminals 1 1...4 mm<sup>2</sup> - cable stiffness: solid without-cable end</p> <p>Control circuit: screw clamp terminals 2 1...4 mm<sup>2</sup> - cable stiffness: solid without-cable end</p> <p>Power circuit: screw connection 1 1...35 mm<sup>2</sup> - cable stiffness: flexible without cable end</p> <p>Power circuit: screw connection 2 1...25 mm<sup>2</sup> - cable stiffness: flexible without cable end</p> <p>Power circuit: screw connection 1 1...35 mm<sup>2</sup> - cable stiffness: flexible with cable end</p> <p>Power circuit: screw connection 2 1...25 mm<sup>2</sup> - cable stiffness: flexible with cable end</p> <p>Power circuit: screw connection 1 1...35 mm<sup>2</sup> - cable stiffness: solid without cable end</p> <p>Power circuit: screw connection 2 1...25 mm<sup>2</sup> - cable stiffness: solid without cable end</p> |
| Tightening torque             | <p>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm</p> <p>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver Philips No 2</p> <p>Power circuit: 8 N.m - on EverLink BTR screw connectors - cable 25...35 mm<sup>2</sup> hexagonal screw head 4 mm</p> <p>Power circuit: 5 N.m - on EverLink BTR screw connectors - cable 1...25 mm<sup>2</sup> hexagonal screw head 4 mm</p> <p>Control circuit: 1.7 N.m - on screw clamp terminals - with screwdriver-pozidriv No 2</p> <p>Power circuit: 2.5 N.m - on screw clamp terminals - with screwdriver-pozidriv No 2</p>   |
| Auxiliary contact composition | 1 NO + 1 NC   |
| Auxiliary contacts type       | Type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1<br>type mirror contact 1 NC conforming to IEC 60947-4-1  |
| Signalling circuit frequency  | 25...400 Hz   |
| Minimum switching voltage     | 17 V for signalling circuit   |
| Minimum switching current     | 5 MA for signalling circuit   |
| Insulation resistance         | > 10 MOhm for signalling circuit  |
| Non-overlap time              | 1.5 Ms on de-energisation between NC and NO contact<br>1.5 Ms on energisation between NC and NO contact   |
| Mounting support              | Plate<br>Rail   |

## Environment

|   |   |
|---|---|
| Standards   | <p>CSA C22.2 No 14</p> <p>EN 60947-4-1</p> <p>EN 60947-5-1</p> <p>IEC 60947-4-1</p> <p>IEC 60947-5-1</p> <p>UL 508</p> <p>IEC 60335-1</p>   |
| Product certifications                                | CSA[RETURN]CCC[RETURN]JUL[RETURN]GOST   |
| IP degree of protection                               | IP20 front face conforming to IEC 60529   |
| Protective treatment                                  | TH conforming to IEC 60068-2-30   |
| Climatic withstand                                    | Conforming to IACS E10 exposure to damp heat<br>conforming to IEC 60947-1 Annex Q category D exposure to damp heat  |
| Permissible ambient air temperature around the device | -40...60 °C<br>60...70 °C with derating   |
| Operating altitude                                    | 0...3000 m  |
| Fire resistance                                       | 850 °C conforming to IEC 60695-2-1  |
| Flame retardance                                      | V1 conforming to UL 94  |
| Mechanical robustness                                 | <p>Vibrations contactor open (2 Gn, 5...300 Hz)</p> <p>Vibrations contactor closed (4 Gn, 5...300 Hz)</p> <p>Shocks contactor closed (15 Gn for 11 ms)</p> <p>Shocks contactor open (10 Gn for 11 ms)</p> |
| Height  | 122 Mm  |
| Width   | 55 Mm   |

|            |         |
|------------|---------|
| Depth      | 120 Mm  |
| Net weight | 0.85 Kg |

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 6.2 Cm   |
| Package 1 Width              | 13.7 Cm  |
| Package 1 Length             | 15.5 Cm  |
| Package 1 Weight             | 927.0 G  |
| Unit Type of Package 2       | S02      |
| Number of Units in Package 2 | 10       |
| Package 2 Height             | 15.0 Cm  |
| Package 2 Width              | 30.0 Cm  |
| Package 2 Length             | 40.0 Cm  |
| Package 2 Weight             | 9.969 Kg |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>   |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| PVC free                   | Yes   |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Product Life Status : **Commercialised**