

Product data sheet Characteristics

LE1M35N710 Enclosed DOL Starter, TeSys LE, 2.6...3.7 A, 415 V AC coil

Main	
Range	TeSys
Product name	TeSys LE
Device short name	LE1M
Product or component type	Enclosed DOL starter
Device application	Standard
Utilisation category	AC-3
Device composition	Contactor Earth terminal Neutral terminal Thermal overload relay
Thermal protection adjustment range	2.63.7 A
Motor power kW	0.55 KW at 240 V AC 50/60 Hz 1.5 KW at 415 V AC 50/60 Hz 0.55 KW at 220/230 V AC 50/60 Hz 1.5 kW at 380/400 V AC 50/60 Hz
[Uc] control circuit voltage	415 V AC 50/60 Hz
Control type	Push-button start green I Push-button stop/reset red O

Complementary

Operating: LED (yellow)	
2 ISO20 top	
2 ISO25 top	
2 Pg 13 top	
2 Pg 21 top	
2 ISO20 bottom	
2 ISO25 bottom	
2 Pg 13 bottom	
2 Pg 21 bottom	
2 Pg 16 top	
2 Pg 16 bottom	
78 mm	
160 mm	
108 mm	
0.6 kg	
-	2 ISO20 top 2 ISO25 top 2 Pg 13 top 2 Pg 21 top 2 ISO20 bottom 2 ISO25 bottom 2 Pg 13 bottom 2 Pg 13 bottom 2 Pg 16 top 2 Pg 16 top 2 Pg 16 bottom 78 mm 160 mm

Environment

Material	ABS (acrylonitrile butadiene-styrene)	
IP degree of protection	IP65 conforming to IEC 60529	
Standards	IEC 60947-4-1	
Ambient air temperature for operation	-540 °C	
Environmental characteristic	Standard environment	
Product certifications	UKCA	

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.7 cm
Package 1 Width	16.5 cm
Package 1 Length	8.3 cm
Package 1 Weight	576.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	6
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.762 kg

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
Sustainable packaging	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₽¥Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------