Product data sheet Characteristics

LE1M35N712

TeSys LE - enclosed DOL starter - 3.7...5.5 A -415 V AC coil



Main Range **TeSys** Product name TeSys LE LE1M Device short name **Enclosed DOL starter** Product or component type Device application Standard Utilisation category AC-3 Device composition Contactor Earth terminal Neutral terminal Thermal overload relay 3.7...5.5 A Thermal protection adjustment range Motor power kW 0.75 KW at 240 V AC 50/60 Hz 2.2 KW at 415 V AC 50/60 Hz 1.1 KW at 220/230 V AC 50/60 Hz 2.2 kW at 380/400 V AC 50/60 Hz [Uc] control circuit 415 V AC 50/60 Hz voltage Control type Push-button start green I

Push-button stop/reset red O

Complementary

Operating: LED (yellow)	
2 ISO20 top	
2 ISO25 top	
2 Pg 13 top	
2 Pg 21 top	
2 ISO20 bottom	
2 ISO25 bottom	
2 Pg 13 bottom	
2 Pg 21 bottom	
2 Pg 16 top	
2 Pg 16 bottom	
78 mm	
160 mm	
108 mm	
0.6 kg	
-	2 ISO20 top 2 ISO25 top 2 Pg 13 top 2 Pg 21 top 2 ISO20 bottom 2 ISO25 bottom 2 Pg 13 bottom 2 Pg 13 bottom 2 Pg 16 top 2 Pg 16 top 2 Pg 16 bottom 78 mm 160 mm

Environment

Material	ABS (acrylonitrile butadiene-styrene)	
IP degree of protection	IP65 conforming to IEC 60529	
Standards	IEC 60947-4-1	
Ambient air temperature for operation	-540 °C	
Environmental characteristic	Standard environment	
Product certifications	UKCA	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	589.0 g
Package 1 Height	8.5 cm
Package 1 width	11.5 cm
Package 1 Length	16.5 cm
Unit Type of Package 2	S02
Number of Units in Package 2	6
Package 2 Weight	3.75 kg
Package 2 Height	15.0 cm
Package 2 width	30.0 cm
Package 2 Length	40.0 cm

Offer Sustainability

REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant E EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☑ China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months	