

## Product data sheet

### Characteristics

# LV432591

ComPacT, Short terminal shield, ComPacT  
NSX400/630, pitch 45mm, IP40, 3 poles



### Main

Product or component type	Short terminal shield
Range compatibility	ComPacT new generation (ComPacT NSX400 new generation) ComPacT new generation (ComPacT NSX630 new generation) ComPacT (ComPacT NSX400) ComPacT (ComPacT NSX630) ComPacT new generation (ComPacT NSX DC new generation) NSX400 DC ComPacT new generation (ComPacT NSX DC new generation) NSX630 DC ComPacT Compact NSX400 DC ComPacT Compact NSX630 DC EasyPact (EasyPact CVS400) EasyPact (EasyPact CVS630) PowerPact (PowerPact L)
Accessory / separate part type	Insulation accessories
Poles description	3P
Quantity per set	1

### Complementary

Connection pitch	45 mm
IP degree of protection	IP40 conforming to IEC 60529

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.100 cm
Package 1 Width	21.900 cm
Package 1 Length	11.900 cm
Package 1 Weight	114.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	20
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	2.767 kg
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Height	50.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	34.136 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------