## Product data sheet Characteristics

# MB224C31

Acti9, MB Encapsulated distribution board, Acti9, 24 poles, 160A main switch, 18mm, IP42, grey



#### Main Range Product name Acti9 encapsulated DB Device short name MB Product or component Distribution board type Device application Distribution Enclosure type Standard Door type External plain Provided equipment Pole filler Circuit schedule card Enclosure Door Removable gland plates Keys Chassis 2 earth/neutral terminal block - top and bottom 165 A DIN rail Main switch Colour Grey

### Complementary

[Ue] rated operational voltage	415 V
Network frequency	50 Hz
[le] rated operational current	160 A
Breaking capacity	25 kA
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Enclosure mounting	Surface
Poles description	3P + N
Enclosure material	Steel
Outgoer Pole capacity	24 x 18 mm
Enclosure material	steel
Height	750 mm
Width	580 mm
Depth	235 mm
IP degree of protection	IP42

### **Packing Units**

PCE	
1	
75.0 cm	
58.0 cm	
23.5 cm	
35.114 kg	
	1 75.0 cm 58.0 cm 23.5 cm

Not applicable, out of EU RoHS legal scope