## **Product datasheet**

Specifications



# current transformer tropicalised DIN mount 100 5 for cables d. 21

METSECT5CC010

| Range                     | PowerLogic  |
|---------------------------|---|
| Product name              | СТ  |
| Product or component type | Current transformer   |
| Secondary current         | 5 A   |
| Accuracy class            | Class 0.5 at 2 VA<br>Class 1 at 2.5 VA<br>Class 3 at 3.5 VA |
| [In] rated current        | 100 A   |

| Complementary                               |                              |
|---|------------------------------|
| Current transformer type                    | Tropicalised for cable       |
| Current transformer ratio                   | 100/5                        |
| [Ith] conventional free air thermal current | 6 kA                         |
| Dynamic withstand current                   | 2.5 Ith                      |
| Maximum safety factor                       | 5                            |
| [Ue] rated operational voltage              | < 720 V AC 50/60 Hz          |
| [Ui] rated insulation voltage               | 3 kV                         |
| Mounting mode                               | By screws<br>Clip-on         |
| Mounting support                            | Mounting plate DIN rail      |
| Width                                       | 44 mm outside:               |
| Height                                      | 65 mm outside:               |
| Depth                                       | 30 mm frame:<br>37 mm total: |
| Diameter                                    | 21 mm                        |
| Net weight                                  | 0.19 kg                      |
| [Uimp] rated impulse withstand voltage      | 3 kV                         |
| Electrical insulation class                 | Class B                      |
| Cable outer diameter                        | 21 mm                        |
| Sealing                                     | With                         |

## **Environment**

| Standards                             | VDE 0414<br>IEC 61869-2 |
|---------------------------------------|-------------------------|
| Product certifications                | EAC<br>CE               |
| IP degree of protection               | IP20                    |
| Relative humidity                     | 095 %                   |
| Ambient air temperature for operation | -2560 °C                |

## **Packing Units**

| Unit Type of Package 1       | PCE        |
|------------------------------|------------|
| Number of Units in Package 1 | 1          |
| Package 1 Height             | 5.600 cm   |
| Package 1 Width              | 5.600 cm   |
| Package 1 Length             | 8.400 cm   |
| Package 1 Weight             | 192.000 g  |
| Unit Type of Package 2       | S02        |
| Number of Units in Package 2 | 50         |
| Package 2 Height             | 15.000 cm  |
| Package 2 Width              | 30.000 cm  |
| Package 2 Length             | 40.000 cm  |
| Package 2 Weight             | 9.864 kg   |
| Unit Type of Package 3       | P12        |
| Number of Units in Package 3 | 400        |
| Package 3 Height             | 27.500 cm  |
| Package 3 Width              | 80.000 cm  |
| Package 3 Length             | 120.000 cm |
| Package 3 Weight             | 88.800 kg  |

## Offer Sustainability

| Office Odstalliability     |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACh Regulation           | REACh Declaration   |
| REACh free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant EU RoHS Declaration   |
| Mercury free               | Yes   |
| China RoHS Regulation      | China RoHS declaration  |
| RoHS exemption information | Yes   |
| Environmental Disclosure   | Product Environmental Profile   |
| Circularity Profile        | End of Life Information   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Recommended replacement(s)