

Product data sheet Characteristics

NSYTBS16128

Thalassa, ABS box IP66 IK07 RAL7035 Int.H150W105D80 Ext.H164W121D87 Opaque cover H20





Main

Range	Thalassa
Product name	Thalassa TBS
Device application	Multi-purpose
Category	Industrial box
Height	164 mm
Width	121 mm
Depth	87 mm
Internal height	150 mm
Internal width	105 mm
Internal depth	80 mm
Enclosure mounting	Wall mounted
Device composition	1 body
	1 cover
	4 cover screw
Quantity per set	Set of 2
Body type	One piece moulded
Type of front cover	Low plain cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

Complementary

ABS (acrylonitrile butadiene-styrene)	
Grey (RAL 7035)	
IEC 62208	
TÜV	
Class II	
IP66 conforming to NEMA 4.4X	
IK07 conforming to IEC 62262	
650 °C conforming to IEC 60695-2-11	
-1540 °C	
-2560 °C	
0.32 kg	
	Grey (RAL 7035) IEC 62208 TÜV Class II IP66 conforming to NEMA 4.4X IK07 conforming to IEC 62262 650 °C conforming to IEC 60695-2-11 -1540 °C -2560 °C

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.7 cm	
Package 1 Width	12.1 cm	
Package 1 Length	16.4 cm	
Package 1 Weight	320 g	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months	