

Product data sheet Characteristics

RMXPC1

Connector, Resi MAX, 1P+N, set of 4





Main	
Range	Resi MAX
Product or component type	Connector
Accessory / separate part category	Connection accessory
Quantity per set	Set of 4
Colour	White (RAL 9003)

Complementary

Poles description	1P + N	
Mounting mode	Horizontal	
[le] rated operational current	63 A at 40 °C	
Connections - terminals	Screw clamp terminals 135 mm² rigid	
Tightening torque	4 N.m	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	48.0 g
Package 1 Height	2.6 cm
Package 1 width	3.6 cm
Package 1 Length	10.2 cm
Unit Type of Package 2	S02
Number of Units in Package 2	100
Package 2 Weight	5.255 kg
Package 2 Height	15.0 cm
Package 2 width	30.0 cm
Package 2 Length	40.0 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☐ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.