



LVABC Service Fitting Connectors

■ Industrial Mains Box

The 3 phase industrial mains box was developed to accept the ILC range of connectors to provide additional weather and mechanical protection at the point of attachment for industrial services.

There is no need to strip or use specialist tools like hand or hydraulic compression tools.

Features

- Fully insulated and waterproof connection system
- Designed to house the ILC connectors
- Fully UV stabilised
- Protects connectors from accidental damage or contact
- Ideal for connecting commercial and industrial 200amp services
- Rear entry of consumer mains cable
- Protects consumer mains cables from UV
- Supplied complete with 4 x ILC connectors.



MCB3/4ILCE-3595

Dimensions of MCBILC range are larger than standard MCB range.

ILC635 is not suitable for use in mains connection boxes.

Products on this page are unsuitable for multi-stranded flexible cables.



Product Number	Description	Cable Size (mm ²)	Number ILC included	Pack Size
MCB1/2ILC	Mains box - industrial + 2 x ILC695	6 to 95	2	1
MCB1/2ILC-3595	Mains box - industrial + 2 x ILC3595	35-95	2	1
MCB3/4ILC	Mains box - industrial + 4 x ILC695	6 to 95	4	1
MCB3/4ILC-3595	Mains box - industrial + 4 x ILC 3595	35-95	4	1



Note: Suffix 'E' denotes addition of yellow shear-head indicator.

MCB3/4ILCE-3595
Dimensions

