



UNISTRUT® COMBINATION STRUTS




- A - 867mm²
- kg/m - 6.80kg/m
- I x-x = 1.052 10⁶mm⁴
- Z x-x = 16.990 10³mm³
- r x-x = 34.8mm
- I y-y = 0.261 10⁶mm⁴
- Z y-y = 12.662 10³mm³
- r y-y = 17.4mm



Mass: 6.80kg/m

PL/GB/HG

P5501




Part No.	Material Thickness	Length
P5501-PL	2.5mm	6m
P5501-GB	2.5mm	6m
P5501-HG	2.5mm	6m


L(mm)	F _{max} (kN)	f	f _{max} (mm)	F(kN)
250	2704 (1)		0.03	122.16
500	2704 (1)		0.21	118.17
750	2704		0.71	111.82
1000	20.50		1.27	103.50
1250	16.40		1.98	93.71
1500	13.67		2.86	82.98
1750	11.72		3.89	71.88
2000	10.25		5.08	60.91
2250	9.11 (2)		6.43	50.48
2500	8.20 (2)		7.93	41.04
2750	7.46 (2)		9.60	33.92
3000	6.83 (2)		11.42	28.50

(1) See Note 1 Page 9
(2) See Note 2 Page 9


OPTIONAL COMBINATIONS




P1001A




P1001B




P1001C




P1001C 41




P1003



P2001A



P4002-1



P2001C3

